Product data sheet Characteristics



865-2524-61

Conext SW - inverter / charger SW 2524 230 input: 20-34 VDC



Main

Conext SW	
SW 2524	
Inverter/Charger	
	SW 2524

Complementary

Type of signal	True sine wave (invert mode)
Continuous power	2800 W overload for output (invert mode) , duration: 30 min 5000 W surge for output (invert mode) , duration: 5 s 2500 W for output (invert mode)
Peak output current	24.3 A for short circuit
Network frequency	50/60 Hz for output (selectable)
Output voltage	230 V AC (invert mode) 1232 V DC (charge mode) 24 V DC (charge mode) for nominal mode
Output current	65 A (charge mode)
Input voltage	170270 V AC (charge mode) 2034 V DC (invert mode) 240 V AC (charge mode) 120 V AC (charge mode)
Input current	10.6 A (charge mode)
Efficiency	90 % (charge mode) 91.5 % (invert mode)
Cos phi	> 0.98 for input
Power consumption in W	< 8 W for search mode
Battery type	FLA Gel AGM
Relay type	Automatic transfert relay at 30 A
Transfer time	<= 20 ms
Provided equipment	Battery temperature sensor included for temperature compensation
Height	418 mm
Width	341 mm
Depth	197 mm
Product weight	22.3 kg

Environment

Environment		
Ambient air temperature for operation	-2060 °C	
Ambient air temperature for storage	-4085 °C	
Standards	IEC/EN 62109-1 IEC/EN 62109-2	
Product certifications	CE RCM	

www.ecovolt.ro



The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.