# **PS4000 C-SJ30-2**

Solar Submersible Pump System for 6" wells

## **System Overview**

Head Flow rate

max. 22 m max, 45 m<sup>3</sup>/h

## **Technical Data**

#### **Controller PS4000**

- Control inputs for dry running protection, remote control etc.
- · Protected against reverse polarity, overload and overtemperature
- Integrated MPPT (Maximum Power Point Tracking)

Power	max. 4.0 kW
Input voltage	max. 375 V
Optimum Vmp*	> 238 V
Motor current	max. 15 A
Efficiency	max. 98 %
Ambient temp.	-3050 °C
Enclosure class	IP54

#### Motor ECDRIVE 4000-C

- · Maintenance-free brushless DC motor
- Water filled
- Premium materials, stainless steel: AISI 304/316
- · No electronics in the motor

Rated power	3.5 kW
Efficiency	max. 92 %
Motor speed	9003,300 rpm
Insulation class	F
Enclosure class	IP68
Submersion	max. 250 m


#### Pump End PE C-SJ30-2

- Non-return valve
- Premium materials, stainless steel: AISI 304
- Optional: dry running protection .
- Centrifugal pump

#### Pump Unit PU C-SJ30-2 (Motor, Pump End)

Borehole diameter	min. 6,0 in
Water temperature	max. 50 °C

## **Standards**



Meets the requirements of:


IEC/EN 61702:1995. IEC/EN 62253 Ed.1

The logos shown reflect the approvals that have been granted for this product family. Products are ordered and supplied with the approvals specific to the market requirements.

\*Vmp: MPP-voltage under Standard Test Conditions (STC): 1000 W/m² solar irradiance, 25 °C cell temperature

BERNT LORENTZ GmbH & Co. KG Kroegerskoppel 7, 24558 Henstedt-Ulzburg, Germany, Tel +49 (0)4193 7548-0, Fax -29, www.lorentz.de










LORENTZ





## PS4000 C-SJ30-2

Solar Submersible Pump System for 6" wells





### **Dimensions and Weights**





D1 = 150 mm





Net weight

Controller	9.0 kg
Pump Unit	20 kg
Motor	10 kg
Pump End	9.5 kg

\*Vmp: MPP-voltage under Standard Test Conditions (STC): 1000 W/m<sup>2</sup> solar irradiance, 25 °C cell temperature

#### BERNT LORENTZ GmbH & Co. KG

Kroegerskoppel 7, 24558 Henstedt-Ulzburg, Germany, Tel +49 (0)4193 7548-0, Fax -29, www.lorentz.de Created by LORENTZ COMPASS 3.0.10.92



All specifications and information are given with good intent, errors are possible and products may be subject to change without notice. Pictures may differ from actual products depending on local market requirements and regulations.